



## Operating Instructions

### ENGLISH

Congratulations on your purchase of the Micralite Toro. The Toro has been designed for safety, comfort and ease of use. We hope you and your child enjoy the freedom provided by the Micralite Toro.

If you have any questions or comments we will be pleased to help; [info@micralite.com](mailto:info@micralite.com)

The Toro is suitable from birth with the use of the Micralite Toro carrycot or the Maxi-cosi Cabriofix car seat\*. We recommend that the Toro seat is used as soon as your child is able to sit up unassisted, usually around 6 months.

#### General Information

**IMPORTANT: READ THESE INSTRUCTIONS CAREFULLY BEFORE USE AND KEEP FOR FUTURE REFERENCE.** Your child's safety may be affected if you do not follow these instructions.

Maximum weight in seat not to exceed 15kg. Maximum weight in the underseat bag not to exceed 2kg evenly distributed. No bag to be hung from the handlebar or more than one child carried at a time, as to do so will adversely affect the stability and safety of the stroller.

Always remove child from the stroller before ascending or descending stairs or escalators.

**WARNING: A CHILD'S SAFETY IS YOUR RESPONSIBILITY**  
**WARNING: IT MAY BE DANGEROUS TO LEAVE YOUR CHILD UNATTENDED**

Children should be harnessed at all times and should never be left unattended. The child should be kept clear of all moving parts while making adjustments. Overloading, incorrect folding and the use of non-approved accessories may damage or break this vehicle.

\*Maxi-Cosi is the trademarks of their respective owners. They are not associated with Micralite Limited and no approval or endorsement by them is to be implied.

**WARNING:** This stroller should not be used near an open fire or exposed flame

**WARNING:** Check that the seat unit attachment devices are correctly engaged before use.

**WARNING:** Ensure that all locking devices are engaged before use

**WARNING:** Any load attached to the handle affects the stability of the pushchair

**WARNING:** Always use the crotch strap in combination with the waist belt.

**WARNING:** This product is not suitable for running or skating.

#### General care and maintenance

Tyre pressures - Keep tyres inflated to 1.5 bar (22psi) using pump supplied (adaptor in handle)  
Punctures can be repaired at any cycle shop.

Always lift the front wheel over kerbs and steps, as repeated impact may cause damage  
Clean the frame with warm water, pay particular attention to washing away any sand or mud from sliding parts of frame.

Never use strong detergent or solvents

Always allow seat and raincover to dry before folding

Clean the seat, hood and raincover with a damp cloth - do not use strong detergents or solvents  
It is unsafe to use spare parts and accessories other than those supplied by Micralite

Manufactured by Micralite Limited, TN3 9BD. This product is designed and manufactured to comply with AS/NZ 2088:2000. BS 7409:1996. EN 1888: 2003. Micralite Limited have the right to make changes to any of their products as part of continuing development and improvement.

For further information please contact Micralite Limited  
T 01892 615900 E [info@micralite.com](mailto:info@micralite.com) I [www.micralite.com](http://www.micralite.com)

- 1 Preparing the stroller for use:** Please refer to the illustrations. Once out of the box, remove the two protectors from the end of the rear axle and discard. Attach the rear wheels by sliding them onto the rear axle as shown **A**. Press the wire clip **B** towards the centre of the wheel to allow the wheel to fully engage. Check the wheel is firmly connected.
- 2 To open the stroller**  
With the stroller standing upright and brake **I** applied, squeeze recline lock plungers **C** & **D** together on both sides and push down, which in turn will open out the front legs of the stroller. Push all the way down until 2 clicks are heard. Please ensure that latch **E** has engaged with bar **D**. By squeezing recline lock plungers again, the seat can then be adjusted to the required angle of recline. The stroller is now ready for your child.
- 3 To fold the stroller**  
If open, fold the canopy **H** and remove the raincover. If locked, release the front wheel swivel locks **S**. Press down lever **F**, then at the same time lift handle **E**. Then depress the lever marked "Press". These actions will disengage the safety locks. Pull up handle **E** in a swift movement to fold. (Tip - pulling the stroller in a backward direction will orientate the front wheels easing the folding action)  
Push in the seat from the front until a click is heard. The stroller is now locked in the closed position. Fold bumper bar **J** flat by rotating upwards.
- 4 Adjusting the Handlebar**  
Loosen the 2 bolts on the handlebar clamps **G**, using allen key supplied. Adjust to required position and tighten bolts.
- 5 To operate the brake**  
To engage brake - with foot push down pedal **I** until click is heard. Ensure both wheels are properly locked by rocking the stroller back and forth with the pedal engaged. To release the brake, lift pedal **I** with the foot.
- 6 To adjust the recline of the seat back**  
Squeeze recline lock plungers **C** & **D** together and either push down or pull upwards until required angle of recline is achieved. Please ensure that recline locks positively click into position.
- 7 To operate and adjust the harness**  
To release the harness, depress the button in the middle of buckle **K**.  
To fasten the harness, slide both fasteners **L** into the buckle until a click is heard.  
To adjust the length of the waist straps, press button **N** and slide adjuster **M** to the required length.  
To adjust the length of the shoulder straps, slide adjuster **O** to the required length.  
The shoulder and waist strap should fit your child snugly.  
Additional D rings **P** are included for the attachment of a separate harness which must conform to BS 6684
- 8 To operate the front wheel swivel locks**  
To engage the swivel locks, push the stroller forwards to align the front wheels, then simply push down on wheel lock **S** until it clicks in place.  
To disengage locks, lift wheel lock **S**.
- 9 Removal of hood and bumper bar**  
Unclip buckle **Q** at rear of hood then alternately press in the 2 white buttons on either side of the stroller, then lift off the hood and bumper bar assembly holding the bumper bar **J** and pulling in a forward direction. To replace, simply push back into position until a click is heard. The bumper bar can be removed from the hood by rotating in an upward movement until it comes to a stop, then flexing out the sides of the hood will allow the bumper bar to be released. Reverse this operation to refit the bumper bar.
- 10 Removal of the fabric seat**  
With the hood removed, release zip **R** at back of seat unit and peel fabric off the frame. Release buckle **T** on the underside of the seat pad, and from behind, push fabric foot well forward. Pull the seat unit from the front away from the tubular frame.
- 11 To convert the stroller for use with the carry cot and Maxi-cosi Cabriofix car seat**  
With the hood and seat unit removed, depress the 2 sprung buttons **V** simultaneously and push in the "U" shaped tube until it is fully engaged. The carry cot/car seat adaptors are then clicked into position as shown **W**.
- 12 Fitting the raincover**  
Zip the raincover onto the hood **H**, then stretch around the bottom of the seat unit.

